

TOLEDO™

GLAZED CERAMIC

4 Colors 3 Sizes $\frac{5}{16}$ " Thickness 1 Mosaic




17" x 17"



13" x 13"




7" x 7"




13" x 13" Mesh




Color shade variations




MSDS Sheet available for download at
www.emser.com




Beige
17" x 17" F84TOLEBE1717
13" x 13" F84TOLEBE1313
7" x 7" F84TOLEBE0707



Walnut
17" x 17" F84TOLEWA1717
13" x 13" F84TOLEWA1313
7" x 7" F84TOLEWA0707



Bruno
17" x 17" F84TOLEBR1717
13" x 13" F84TOLEBR1313
7" x 7" F84TOLEBR0707



Noce
17" x 17" F84TOLENO1717
13" x 13" F84TOLENO1313
7" x 7" F84TOLENO0707

MOSAICS



Mosaic Blend 2"x2" on
13"x13" mesh
F84TOLEMC1313MOB

TRIMS



Floor SBN 3"x13"



V Cap 2"x7"



V Cap Corner 2"x2"



Wall DBN 7"x7"



Wall SBN 7"x7"



Quarter Round 1"x7" Beak 1"x1"

APPLICATIONS

Product	Floor	Wall	Counter	Residential	Commercial Light	Commercial Heavy	Outdoor use	Go Linear	Green Friendly
TOLEDO™	X	X		X	X				

TECHNICAL SPECIFICATIONS

TEST	ASTM #	RESULTS
Abrasion Resistance	C1027	III
Breaking Strength	C648	≥ 450 lbf.
Chemical Resistance	C650	NON-RESISTANT
Water Absorption	C373	> 3%
Coefficient of Friction SCOF	C1028	Wet ≥ .60
Coefficient of Friction DCOF	BOT3000	Wet ≥ .42
Freeze-Thaw Cycling	C1024	NON-RESISTANT
Scratch Hardness	MOHS	7

GROUT JOINT RECOMMENDATION

Approximately 3/16"

PATTERN SUGGESTIONS

